Ψ Capacitor Tactical Module

Carlos Omeñaca Prado

November 2025



Figure 1: Ψ-Capacitor Mk VI — Field-Grade Coherent-Pressure Storage Unit

Contents

1 General Description 3

2 Upper Assembly: Coherent Pressure Chamber 3

3 Primary Chassis (Mk VI Standard Body) 3

4 Engraved Technical Indicators 4

5 Mechanical Platform 4

6 Catalog Tagline 4

1 General Description

The **Ψ-Capacitor Mk VI** is a **high-density coherent-pressure storage module** engineered for large-power laser assemblies and field-campaign energy systems. It operates as a **buffer reservoir for longitudinal Ψ-mode pressure**, delivering stable, ripple-free output for high-demand laser cannons and multi-module emitter arrays.

Its geometry, mass distribution, and connector layout follow the **Mk VI industrial standard**, ensuring full interoperability with existing Ψ-Cell and Ψ-Coil architectures.

2 Upper Assembly: Coherent Pressure Chamber

A reinforced, dark-anodized cylindrical housing with deep finning:

- **COHERENT PRESSURE CHAMBER — Mk VI**
- **/ EM SHIELDING / HIGH-DENSITY STORAGE**

The top plate includes:

- **SYNC / PIEZO-CLK-Ψ Port**
  Synchronization interface for piezo-driven phase alignment and external trigger systems.
- Hex-profile sealing gland identical to all Mk VI field modules.

This chamber provides **ultra-low-loss containment** for longitudinal Ψ-waves and stabilizes pressure-field uniformity during high-power discharge.

3 Primary Chassis (Mk VI Standard Body)

A cubic, shock-resistant enclosure with:

- reinforced corner posts,
- black torx structural hardware,
- modular industrial connectors.

Front/Side Ports:

- **OUTPUT / HIGH-DENSITY Ψ-FEED**
  Supplies coherent pressure to downstream modules (emitters, coils, cannons).
- **CALIBRATION / ZERO-Ψ**
  Dual-stage calibration for null-bias alignment and chamber balancing.
- **PIEZO INPUT / SYNC**
  Accepts wideband piezo-modulated drive signals for forced Ψ-mode compression or synchronized discharge cycles.

4 Engraved Technical Indicators

Laser-engraved labeling:

- **FIELD-CAMPAIGN MODEL — Mk VI**
- **PRESSURE-STABILITY REGION** — $\tau \approx 6$ mm; $L \approx 45$ mm
- **COHERENT PRESSURE STORAGE UNIT**

These indicators identify confinement depth, storage capacity, and operational tolerances.

5 Mechanical Platform

The lower section incorporates:

- vibration-isolated feet for field deployment,
- armored housing for impact resistance,
- micro-perforated panels for **surface-charge equalization** (non-thermal venting),
- standard Mk VI mounting grid for multi-unit racks or mobile weapons platforms.

6 Catalog Tagline

A high-density Mk VI coherent-pressure capacitor engineered for mega-laser assemblies, providing stabilized Ψ-mode storage and synchronized high-power discharge for THz/IR emitters and field-grade directed-energy platforms.

References

[1] Omeñaca Prado, Carlos (2025). *Batería Cuárquica de Presión Coherente (Ψ-Cell).* Internet Archive.

Available at: https://archive.org/details/bateria-de-presion-coherente

[2] Omeñaca Prado, Carlos (2025). *PSI Coil The Cylindrical Converter Of Coherent Pressure Complete Physical Functional And Electrical Specification.* Internet Archive.

Available at: https://archive.org/details/psi-coil-the-cylindrical-converter-of-coherent-pressure-complete-physical-functi

[3] Omeñaca Prado, Carlos (2025). *Seven New Classes of LASER Diodes Enabled by Graphene and the Psi-Field: A Quarkbase Cosmology Framework*. Internet Archive.

Available at: https://archive.org/details/seven-new-classes-of-laser-diodes

[4] Omeñaca Prado, Carlos (2025). *The Next Electromagnetic Revolution Maxwell S Equations In The Framework Of Quarkbase Cosmology*. Internet Archive.

Available at: https://archive.org/details/the-next-electromagnetic-revolution-maxwell-s-equations-in-the-framework-of-quarkbase-cosmology